

CLAY ARRESTOR INSTALLATION INSTRUCTIONS & USERS GUIDE

Congratulations on choosing a quality product from Southern Cross. This clay ar-
restor has been designed and approved by water board authorities to minimise the
fouling and blocking of the drainage system in buildings. When correctly installed
and maintained this unit will give many years of service and help to protect our en-
vironment.

THE PLUMBER

1. Locate the arrestor in a position that provides a recommended minimum of 300 mm clearance from lid to underside of bench top for removal of inner tank.
2. Connect 50mm trap to sink bowl and ensure water level of "S" trap is a minimum 200mm above water level of arrestor.
3. Test all connections for leaks.

THE USER

1. Do not dispose of acids, chemicals or any other substance unsuitable for normal sink waste through this arrestor.
2. Do not dispose of large quantities of clay through this trap.
3. Do not dispose of food scraps through this arrestor.
4. When washing down implements used with clay ensure enough water is used to clear the "S" trap.
5. Maintenance will depend on usage, the arrestor used daily with high volumes of clay will require more frequent cleaning.

MAINTENANCE INSTRUCTIONS

1. Disconnect inlet & remove lid. .
2. Remove basket & clean.
3. Should the arrestor itself need cleaning, proceed as follows:-
4. Drain the tank before disconnecting.
5. Remove the tank and clean as required.



**23-27 Clapham Road
Regents Park NSW 2143**

Ph: 02 9644 2811

Fx: 02 9645 1114